

CMOS/ 1.8V, 2.5V, 3.3V Compatible/ 2.5×2.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
2.5 (L) ×2.0 (W) ×0.7 (H) mm (Typ.)
- Highly reliable with seam welding
- CMOS output
- Supply voltage 1.8/ 2.5/ 3.3V
Wide operating voltage range 1.6 to 3.63V
- Low current consumption
- High output frequency 125MHz

How to Order

KC2520B 25.0000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (2.5×2.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V, 2.5V, 3.3V Compatible)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ Enable Function (45/ 55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000 pcs./ reel)

Table 1

Freq. Tol. Code	× 10 ⁻⁶	Operating Temperature Range (°C)	Note
O	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	±100	-40 to +85	With only certain frequencies
G	± 50		


Specifications

Item	Symbol	Conditions	Specifications		Units	
			Min.	Max.		
Output Frequency Range	f _o		1.5	125	MHz	
Frequency Tolerance	f _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Aging (1 year @25°C), Shock and vibration	Op.Temp.: -40 to +85°C Op.Temp.: -10 to +70°C Op.Temp.: -10 to +70°C	-100 -50 -30	+100 +50 +30	×10 ⁻⁶
Storage Temperature Range	T _{stg}		-55	+125	°C	
Operating Temperature Range	T _{use}	Standard Specifications Extend (Option)	-10 -40	+70 +85	°C	
Max. Supply Voltage	—	1.5≤f _o ≤60MHz 60<f _o ≤125MHz	-0.5 -0.5	+6.0 +4.0	V	
Supply Voltage	V _{cc}		1.6	3.63	V	
Current Consumption (Maximum Loaded/ 1.6≤V_{cc}≤2.0V)	I _{cc}	1.5≤f _o ≤24MHz	—	2.5	mA	
		24<f _o ≤40MHz	—	3.5		
		40<f _o ≤60MHz	—	5		
		60<f _o ≤80MHz	—	6		
		80<f _o ≤100MHz	—	10		
		100<f _o ≤125MHz	—	12		
Current Consumption (Maximum Loaded/ 2.0<V_{cc}≤2.8V)	I _{cc}	1.5≤f _o ≤24MHz	—	3	mA	
		24<f _o ≤40MHz	—	4.5		
		40<f _o ≤60MHz	—	5		
		60<f _o ≤80MHz	—	6.5		
Current Consumption (Maximum Loaded/ 2.8<V_{cc}≤3.63V)	I _{cc}	80<f _o ≤100MHz	—	11	mA	
		100<f _o ≤125MHz	—	13.5		
		1.5≤f _o ≤24MHz	—	3.5		
		24<f _o ≤40MHz	—	5		
Stand-by Current	I _{std}		—	10	μA	
Symmetry	SYM	@50%V _{cc}	45	55	%	
Rise/ Fall Time (10% V_{cc} to 90% V_{cc} Maximum Loaded)	tr/ tf	1.6≤V _{cc} ≤2.0V 2.0<V _{cc} ≤2.8V 2.8<V _{cc} ≤3.63V	— — —	6.5 5 4.5	nS	
Low Level Output Voltage	V _{OL}	I _{OL} =4mA	—	10%V _{cc}	V	
High Level Output Voltage	V _{OH}	I _{OH} =-4mA	90%V _{cc}	—	V	
Output Load	L _{CMOS}	CMOS Output	—	15	pF	
Low Level Input Voltage	V _{IL}		—	30%V _{cc}	V	
High Level Input Voltage	V _{IH}		70%V _{cc}	—	V	
Disable Time	t _{dis}		—	100	nS	
Enable Time	t _{ena}		—	5	mS	
Start-up Time	t _{str}	@ Minimum operating voltage to be 0 sec.	—	10	mS	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

