HellermannTyton

Specification Sheet

Part Number: SNP110M4

Article Number



Snapper Hose Clamp, .24"-.26" Bundle Diameter, POM, White, 1000/pkg

Туре	SNP1

190-00023

Color	White (WH)
-------	------------

Features & Benefits	 Designed for quick, ratcheted installation and can be released and
	reused. • Polyacetal material resists chemicals, corrosion and UV
	rays making it suitable for extreme environments

Quantity Per bag

_							_						
ט	r	\smallfrown	М	П		•	- 11	es	r	rı	n	1	n
		u	u	u	·	L	$\boldsymbol{\omega}$	CO	u		ш	u	

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

Short Description

Snapper Hose Clamp, .24"-.26" Bundle Diameter, POM, White,

1000/pkg

Global Part Name

SNP1-POM-WH

Fixation Method

Plug-in mounting

Variant

Closed

Wall Thickness WT (Imperial)

.04

Wall Thickness WT (Metric)

1.0

Material

Polyacetal (POM)

Material Shortcut

POM

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature (Metric) -40°F to +194°F (-40°C to +90°C)

ROHS Complaint Yes

Package Quantity(Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions