

Support bracket - AB-SK-D TOP INSULATED - 3062087

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Support bracket, Bracket for busbars, set every 20 cm, length: 155.8 mm, width: 5.2 mm, number of positions: 2, color: gray




Your advantages

- ✓ For mounting SK and SKS shield connection clamps
- ✓ Can be labeled with zack marker strip and KLM terminal strip markers
- ✓ Compact design with 5.2 mm pitch
- ✓ Parking option for bridges and plugs
- ✓ The 3 x 10 mm rail can be mounted in the supports vertically, horizontally, and at a 45° angle for optimum conductor placement
- ✓ For user-friendly shield connection, especially for single and multi-level terminal blocks and devices with a front connection



Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 591850
GTIN	4046356591850

Technical data

Dimensions

Length (b)	155.8 mm
Width (a)	5.2 mm

General

Color	gray
Flammability rating according to UL 94	V0
Material	PA
Insulating material	PA

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Support bracket - AB-SK-D TOP INSULATED - 3062087


Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27400607
eCl@ss 4.0	23150300
eCl@ss 4.1	23150300
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27409200
eCl@ss 7.0	27409221
eCl@ss 8.0	27409221
eCl@ss 9.0	27400607

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC002270
ETIM 5.0	EC002270

Support bracket - AB-SK-D TOP INSULATED - 3062087

Classifications

ETIM

ETIM 6.0	EC001166
ETIM 7.0	EC001166

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708
UNSPSC 18.0	39121708
UNSPSC 19.0	39121708
UNSPSC 20.0	39121708
UNSPSC 21.0	39121708

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>